

MATERIAL SAFETY DATA SHEET



PLEDGE - Lemon (Aerosol)

HMIS		NFPA	Personal protective equipment
Health	0	0	None / Aucune / Ninguno
Fire Hazard	4	4	
Reactivity	0	0	

Version Number: 2

Preparation date: 2009-10-23

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PLEDGE - Lemon (Aerosol)
MSDS #: 126026-009
Product Code: 94430, 3694028
Recommended use: Furniture care. Industrial/Institutional.

Manufacturer, importer, supplier:

US Headquarters
 JohnsonDiversey, Inc.
 8310 16th St.
 Sturtevant, Wisconsin 53177-1964
 Phone: 1-888-352-2249
 MSDS Internet Address:
 www.johnsondiversey.com

Canadian Headquarters
 JohnsonDiversey - Canada, Inc.
 2401 Bristol Circle
 Oakville, Ontario L6H 6P1
 Phone: 1-800-668-3131

Emergency telephone number: 1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CONTENTS UNDER PRESSURE. FLAMMABLE.

Principle routes of exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Eye contact: None known.

Skin contact: None known.

Inhalation: None known.

Ingestion: None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

Ingredient(s)	CAS #	Weight %	LD50 Oral - Rat (mg/kg)	LD50 Dermal - Rabbit	LC50 Inhalation - Rat
Butane	106-97-8	1 - 5%	2000	Not available	=658 mg/L (4 h)
Propane	74-98-6	1 - 5%	2400	Not available	=658 mg/L (4 h)
Isobutane	75-28-5	1 - 5%	2000	Not available	=658 mg/L (4 h)

4. FIRST AID MEASURES

Eye contact: Rinse with plenty of water.

Skin contact: Rinse with plenty of water.

Inhalation: No specific first aid measures are required.

Ingestion: No specific first aid measures are required.

Aggravated Medical Conditions: None known.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Dry chemical, water spray, foam, carbon dioxide.

Specific hazards: Aerosol product - Containers may rocket or explode in heat of fire. NFPA 30B Level 1 Aerosol.

Unusual hazards: None known.

Specific methods: Aerosol Product - Containers may rocket or explode in heat of fire. Use water spray to keep fire-exposed containers cool.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Extinguishing media which must not be used for safety reasons: No information available.

6. ACCIDENTAL RELEASE MEASURES

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Remove all sources of ignition. Ensure adequate ventilation.
Environmental precautions and clean-up methods: Soak up with oil absorbent material.

7. HANDLING AND STORAGE

Handling:

CONTENTS UNDER PRESSURE. Do not puncture or incinerate. Keep away from open flames, hot surfaces and sources of ignition. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage:

Store in a cool, dry, well ventilated area away from heat or open flame. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 degrees C or 120 degrees F. Do not pierce or burn, even after use. Protect from freezing. KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

No special ventilation requirements.

Personal Protective Equipment

Eye protection: No special requirements under normal use conditions.
Hand protection: No special requirements under normal use conditions.
Skin and body protection: No special requirements under normal use conditions.
Respiratory protection: No special requirements under normal use conditions.
Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

Ingredient(s)	CAS #	ACGIH	OSHA	Mexico
Butane	106-97-8	1000 ppm (TWA)		1900 mg/m ³ (TWA) 800 ppm (TWA)
Propane	74-98-6	1000 ppm (TWA)	1000 ppm (TWA) 1800 mg/m ³ (TWA)	
Isobutane	75-28-5	1000 ppm (TWA)		

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol	Bulk density:	No information available
pH:	No information available	Dilution pH:	No information available.
Appearance:	Emulsion	Vapor density:	No information available
Color:	White	Evaporation Rate	No information available
Odor:	Lemon	Boiling point/range:	Not determined
Specific gravity:	0.916	Melting point/range:	Not determined
Density:	7.63 lbs/gal 0.916 Kg/L	Decomposition temperature:	Not determined
VOC:	16.8% *	Autoignition temperature:	No information available
Flash point:	<20°F <-6.67°C	Partition coefficient (n-octanol/water):	No information available
Solubility:	Insoluble	Solubility in other solvents:	No information available
Viscosity:	No information available	Elemental Phosphorus:	0% by w.t.

Explosion limits: - lower: Not determined- upper: Not determined

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Stability: The product is stable
Polymerization: Hazardous polymerization does not occur
Hazardous decomposition products: None reasonably foreseeable.
Conditions to avoid: Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

11. TOXICOLOGICAL INFORMATION

Acute toxicity: Oral LD50 estimated to be greater than 5000 mg/kg
Component Information: See Section 3
Chronic toxicity: None known
Specific effects
Carcinogenic effects: None known
Mutagenic effects: None known
Reproductive toxicity: None known
Target organ effects: None known

12. ECOLOGICAL INFORMATION

Environmental Information: No data available

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Dispose of according to all federal, state and local applicable regulations

14. TRANSPORT INFORMATION

DOT/TDG: Please refer to the Bill of Lading/receiving documents for up to date shipping information

15. REGULATORY INFORMATION

International Inventories

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

STATE RIGHT TO KNOW

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
Water	7732-18-5	-	-	-	-
Naphtha, petroleum, light alkylate	64741-66-8	-	-	-	-
Butane	106-97-8	X	X	X	X
Propane	74-98-6	X	X	X	X
Isobutane	75-28-5	X	X	X	-
Silicones	63148-62-9	-	X	-	-

CERCLA/ SARA

SARA 311/312 Hazard Categories

Immediate: -
Delayed: -
Fire: X
Reactivity: -
Sudden Release of Pressure: X

Canada

WHMIS hazard class: A Compressed gases, B5 Flammable aerosol.



WHMIS graphic: Class A Compressed Gases

Ingredient(s)	CAS #	NPRI
Isobutane	75-28-5	X

16. OTHER INFORMATION

Reason for revision: Not applicable

Prepared by: NAPRAC

Additional advice: None

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.